

p/n ASYS-2339-01		DS-IDL8 Discrete Input Module – Low Volt	
Channels	Eight (8)		
Input Voltage Range	5 to 36VAC/DC		
Input Impedance	5K ohms		
Optically Isolated	Yes		
Reverse Polarity Protected	Yes		
Over Voltage Rating	100VAC/DC max.		
Power Consumption	26mA		
p/n ASYS-2340-01		DS-ODK8 Discrete Output Module – 8 Ch, Relay	
Channels	Eight (8)		
Output Terminals	Dry contact (NO)		
Contact Ratings	120VAC/5A		
Power Consumption	10mA @24VDC (outputs OFF) 100mA @24VDC(outputs ON)		
p/n ASYS-2340-01		DS-IAI4 4-20mA Analog Input Module – 4 Ch	
Channels	Four (4)		
Resolution	16-bit		
Input Impedance	125 ohms		
Reverse Polarity Protected	Yes		
Over-Voltage Rating	42VDC max.		
Accuracy	0.2%		
Power Consumption	32mA (inputs disconnected)		
p/n ASYS-2340-01		DS-OAI4 4-20mA Analog Output Module – 4 Ch, ISOL	
Channels	Four (4)		
Resolution	16-bit		
Short-Circuit Protection	Yes		
Optically Isolated	Yes		
Accuracy	0.12%		
Power Consumption	32mA (outputs disconnected)		